

Xiamen Fengtai Energy Technology Co., Ltd

www.solar-wind-e.com


Tlf. 0086 592 5182735

Model	
Monocrystalline Silicon solar panel	ZDNY 75-M

Electrical characteristics	
Max. power Peak (PmW)	75 Watt
Power tolerance (%)	±3%
Max. system voltage VDC	600 Volt
Max. power voltage Vmp (V)	17,3 Volt ± 0,5 volt.
Max power current Imp (A)	4,35 Amp. ± 0,1 Amp.
Open circuit voltage Voc	21,7 Volt ± 0,5 volt.
Short circuit current Isc	4,72 Amp. ± 0,1 Amp.
Diode	2 pcs.
Operation temperature	-40 to + 85° C.

Specification (mechanical characteristics)	
Number, type and arrangement of cells	72 pcs. Monocrystalline silicon (4x9)
Dimensions: L x W x H	1195 x 541 x 35
Weight	8,1 Kg.
Frame (type, material)	Aluminium Alloy - anodized
Front glass	High transmission, low iron, tempered glass 3,2 mm.
Output tolerance	± 3%

Note: Test condition are STC Irradiance 1000 W/m² with AM 1,5 spectrum, cell temperature 25°C. Test method according to IEC 904-1. Tolerance efficiency 5% reel.



- Nominal 12 VDC for standard output.
- Outstanding low light performance.
- Heavy-duty anodized frames.
- High transparent low-iron tempered glass.
- Cells are laminated with TPT and EVA ensuring longer life and maximum performance.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

